

APPLICATION FOR

UNITED STATES LETTERS PATENT

S P E C I F I C A T I O N

Inventors: Ryusuke YAMAGUCHI

Shoichi NAGATOMO

A PORTABLE IMAGE CAPTURING DEVICE

BACKGROUND OF THE INVENTION

5

FIELD OF THE INVENTION

The present invention relates to a portable image capturing device which has an optical communication function, e.g., infrared communication or the like, and an image capturing function, e.g., a digital camera or the like.

DESCRIPTION OF THE PRIOR ART

An optical communication technique which carries out data communication with an external device by using light signal is known.

In the electronic apparatus having such a function, there is a portable electronic apparatus, e.g., a PDA or a digital still camera, having the infrared communication function, to convert data to infrared ray signal and to carry out data communication with the external device by using the signal, as one of optical communication. Such a portable electronic apparatus comprises an infrared ray emitting element having an infrared-emitting diode and the like, for sending infrared ray signal, and an infrared detecting element having a photodiode and the like for receiving the infrared ray signal, as a construction to realize the infrared communication function.

In a portable electronic apparatus having the infrared

communication function, in order to carry out data communication with an external electronic device, e.g., a PC or the like, an infrared communication window comprising transparent parts is formed in a case body, and a cover for
5 infrared communication, which is made by forming an optical filter material is provided on the window, to cover the infrared ray emitting element and the infrared detecting element which are provided inside.

The cover for infrared communication cuts the wavelengths
10 contributing to interruptions for communication during infrared communication, to improve the reliability of data.

In such a portable electronic apparatus having the infrared communication function, in particular, in a capturing device, e.g., digital camera or the like, it is required to
15 provide an infrared communication portion and a camera unit individually. However, it is difficult to arrange the infrared communication portion and the camera unit individually to each other because of ensuring a good portability. Therefore, it is supposed that the problems of inconvenience of user's
20 handling the portable electronic apparatus, e.g., on confirmation of captured images, transmission of capturing image data to an external device, or the like.

25

SUMMARY OF THE INVENTION

An object of the invention is to provide a portable image

capturing device which has an optical communication function, in particular, an infrared communication function, and an image capturing function and which improves the convenience on user's handling.

5 Another object of the invention is to reduce the number of necessary components and the number of steps for assembling by covering both the image capturing portion (camera portion) and the optical communication portion (infrared communication portion) in common by a transparent covering member.

10 The present invention was developed in order to solve the above-described problems. In accordance with one aspect of the present invention, the portable image capturing device, comprises: a device body, an image capturing portion (camera portion) and an optical communication portion (infrared communication portion), which are provided on the device body, and a transparent covering member for covering both the image capturing portion and the optical communication portion, which is provided on the device body.

20 According to the present invention, because the image capturing portion and an optical communication are provided adjacent to each other on the device body, it is possible to improve the convenience on user's handling and to reduce the number of necessary components and the number of steps for assembling by covering both the image capturing portion and the optical communication portion in common by a transparent covering member.

25

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a plan view showing the entirety of a portable
 5 image capturing device, as an embodiment of the invention;

FIG. 2 is an enlarged plan view of the device body shown
 in FIG. 1;

FIG. 3 is a perspective view of the device body shown in
 FIG. 2;

10 FIG. 4 is a front view showing the camera portion and the
 optical communication portion (infrared communication
 portion) in the device body shown in FIG. 3;

FIG. 5 is a side view of the device body shown in FIG.
 4;

15 FIG. 6 is a perspective view of only the device body shown
 in FIG. 3, from the side opposite to the camera portion (image
 capturing portion) and the optical communication portion
 (infrared communication portion) at an angle;

FIG. 7 is a bottom view of the body portion of the device
 20 shown in FIG. 6, in which the camera portion and the optical
 communication portion (infrared communication portion) are
 shown in cross section and the inner module is shown without
 the case back;

FIG. 8 is a cross-sectional view taken on line A-A of FIG.
 25 7;

FIG. 9 is a cross-sectional view taken on line B-B of FIG.
 7;

FIG. 10 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), which are shown in FIG. 4;

5 FIG. 11 is a bottom view of the device body shown in FIG. 6;

FIG. 12 is an exploded perspective view showing the case back, the ring for waterproof, and the battery cover, which are attached to the rear surface of the device body shown in FIG.

10 1;

FIG. 13 is an enlarged perspective view showing the structure of the rear side of the battery cover shown in FIG. 12;

15 FIG. 14 is an exploded perspective view showing the case back shown in FIG. 12;

FIG. 15 is a cross-sectional view taken on line C-C of FIG. 14;

FIG. 16 is a rear view of the case back shown in FIG. 14;

20 FIG. 17 is an enlarged cross-sectional view taken on line D-D of FIG. 16;

FIG. 18A is a front view showing the structure of the battery cover shown in FIG. 13, and FIG. 18B is a rear view thereof;

25 FIG. 19 is a cross-sectional view taken on line E-E of FIG. 18B;

FIG. 20 is an enlarged side view of the "F" portion of FIG. 19;

FIGS. 21A and 21B show the attachment relationship between the battery cover and the case back, from the rear side, in which FIG. 21A is a view when inserting the battery cover into the case back, and FIG. 21B is a view when rotating the battery cover to lock to the case back;

FIG. 22 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the second embodiment of the invention;

FIG. 23 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the third embodiment of the invention;

FIG. 24 is a bottom view of the device body shown in FIG. 23, in which the camera portion and the optical communication portion (infrared communication portion) are shown in cross section;

FIG. 25 is a cross-sectional view taken on line C-C of FIG. 24;

FIG. 26 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the fourth embodiment of the invention;

FIG. 27 is a bottom view of the device body shown in FIG. 26, in which the camera portion and the optical communication portion (infrared communication portion) are shown in cross section;

FIG. 28 is a cross-sectional view taken on line D-D of FIG. 27;

FIG. 29 is a cross-sectional view taken on line E-E of FIG. 27;

5 FIG. 30 is an exploded perspective view showing the cover structure of the camera portion and the optical communication portion (infrared communication portion), as the fifth embodiment of the invention;

10 FIG. 31 is a bottom view of the device body shown in FIG. 30, in which the camera portion and the optical communication portion (infrared communication portion) are shown in cross section;

FIG. 32 is an enlarged plan view of the device body, as the sixth embodiment of the invention;

15 FIG. 33 is an exploded perspective view showing the relationship between the device body shown in FIG. 32 and another infrared communication apparatus;

FIG. 34 is an enlarged plan view of the device body, as the seventh embodiment of the invention; and

20 FIG. 35 is a perspective view of the device body shown in FIG. 34.

DETAILED DESCRIPTION OF THE INVENTION

25

FIRST EMBODIMENT

The first embodiment of the invention will be explained

in detail with reference to the drawings.

FIG. 1 is a plan view showing the entirety of a portable image capturing device, as an embodiment of the invention, in which the reference numeral 1 denotes a wrist watch (portable image capturing device), the numeral 2 denotes a case body (device body), the numerals 3 and 4 denote a pair of wrist bands, and the numeral 5 denotes a loop (band fastening member).

FIG. 2 is an enlarged plan view of the portion of the case body 2, FIG. 3 is a perspective view of the portion of the case body 2, FIG. 4 is a front view showing the camera portion (image capturing portion) and the optical communication portion in the portion of the case body 2, FIG. 5 is a side view of the portion of the case body 2, and FIG. 6 is a perspective view of only the portion of the case body 2, from the side opposite to the camera portion and the optical communication portion at an angle. In these figures, the reference numeral 6 denotes an image capturing lens (camera portion), the numeral 7 denotes an infrared communication portion (optical communication portion), the numeral 8 denotes a case back, the numeral 9 denotes a battery cover, the numeral 21 denotes a transparent covering member, the numeral 22 denotes a data display portion, the numeral 23 denotes a shutter button (shutter operating member), the numeral 24 denotes an adjustment key, the numeral 25 denotes a mode key, the numeral 26 denotes a reverse key, the numeral 27 denotes a display changing key, the numeral 28 denotes a forward key, and the numeral 29 denotes a bezel.

The case body 2 of the wrist watch 1 which is an application

example of the portable image capturing device according to the invention has an end side surface at which a wrist band 3 is attached in the other side of the case body, in FIGS. 1 and 2. In the end side surface, the image capturing lens 6 which is
 5 the camera portion and the infrared communication portion 7 which is the optical communication portion are provided near to each other in parallel, as shown in FIGS. 3 and 4.

In the case body 2, the transparent covering member 21 which covers the image capturing lens 6 and the infrared
 10 communication portion 7 is provided on the end side surface, and the data display portion and the shutter button 23 are provided on the upper surface. The shutter button 23 is positioned in the opposite side to the image capturing lens 6 and the infrared communication portion 7 with respect to the
 15 data display portion 22. Shutter operation can be carried out by pushing the shutter button 23 toward the rear surface from the front surface in FIG. 3.

In a side surface of the case body 2, the adjustment key 24 and the mode key 25 are provided. In the other side surface
 20 of the case body 2, the reverse key 26, the display changing key 27, and the forward key 28 are provided. The reverse key 26 and the display changing key 27 are for making the data display portion 22 display a plurality of stored images and change them.

On the rear surface of the case body 2 near the transparent
 25 covering member 21, a pair of projecting band attachment portions 201 and 201 for attaching the wrist band 3 in the side of the image capturing lens 6 and the infrared communication

portion 7 are provided, as shown in FIGS. 3-6. Between the pair of projecting band attachment portions 201 and 201, a band attachment bar 203 is attached. Therefore, the wrist band 3 attached to the band attachment bar 203 can be rotated on the attachment bar 203 to be overlapped on the rear surface of the case body 2, as shown by a line for supposition (two-dot chain line) in FIG. 5.

On the upper surface of the case body 2, the bezel 29 is assembled for shock resistance. To the rear surface of the case body 2, the case back 8 is locked securely by screws. To the central portion of the case back 8, the battery cover 9 is attached, as described later.

The attachment position of the band attachment bar 203 may be positioned in the rear surface side than the battery cover 9.

FIG. 7 is a bottom view showing the inner module in the case body 2 without the case back, in which the main portion is shown in cross section, FIG. 8 is a cross-sectional view taken on line A-A of FIG. 7, FIG. 9 is a cross-sectional view taken on line B-B of FIG. 7, and FIG. 10 is an exploded perspective view showing the cover structure of the image capturing lens 6 and the infrared communication portion 7. In these figures, the reference numeral 11 denotes a module, the numeral 12 denotes a board, the numerals 13 and 14 denote housings, the numeral 15 denotes a circuit supporter, the numeral 16 denotes a connector socket, the numeral 17 denotes a battery insertion portion, the numerals 61 denote solder balls (electric

conductive member), the numeral 62 denotes an electrode film, the numeral 63 denotes a connector, the numeral 71 denotes an infrared emitting element, the numeral 72 denotes an infrared detecting element, the numeral 73 denotes a cover for infrared communication (filter member), and the numerals 89 and 99 denote O-rings (water proof members).

The module 11 has functions of watch, transmission and data display. The module 11 comprises the board 12 which has a various types of electronic components mounted thereon, the housings 13 and 14 provided in both sides thereof, the circuit supporter 15 provided in the rear side of the board 12, and the like. In a cut-out portion at a corner of the module 11, a connector socket 16 is provided, and at a central portion of the circuit supporter 15, the battery insertion portion 17 is provided.

The image capturing lens 6 is fitted into a capturing window 206 of the case body 2. The infrared communication portion 7 is disposed in a communication window 207 of the case body 2. The transparent covering member 21 is attached into a recess portion 205 for cover attachment, which opens in the end side surface of the case body 2, to cover both the image capturing lens 6 and the infrared communication portion 7.

In the image capturing lens 6, a CMOS (Complementary Metal-Oxide Semiconductor) for data conversion of signals from the infrared detecting element and for transfer thereof is installed. The electrode film 62 is connected with the image capturing lens 6 through many solder balls 61 which are the

electric conductive member. The electrode film 62 is provided with a connector 63 at the end thereof.

The image capturing lens 6 is fitted in the capturing window 206 of the case body 2 before incorporating the module 11 into the case body.

The infrared communication portion 7 comprises the infrared emitting element 71 and the infrared detecting element 72, which are attached to the module 11. The module 11 is incorporated into the case body 2 so that the infrared emitting element 71 and the infrared detecting element 72 which make a pair are inserted into the communication window 207 of the case body 2.

After the connector 63 attached to the end of the electrode film 62 is fitted and connected to the connector socket 16 of the module 11, the case back 8 is locked securely by screws to the rear surface of the case body 2. Between the case body 2 and the case back 8, the O-ring (water proof ring) 89 is sandwiched and between the case back 8 and the battery cover 9, the O-ring (water proof ring) 99 is sandwiched.

Then, the periphery of the cover 73 for infrared communication which is a filter member is melted and fixed to the periphery of the communication window 207, as shown in FIG. 10. Further, the periphery of the transparent covering member 21 having a convex lens shape is melted and fixed to the periphery of the recess portion 205 for cover attachment, to cover both the image capturing lens 6 and the infrared communication portion 7.

The transparent covering member 21 has a circular recess portion 211 on the front surface at a position corresponding to that of the image capturing lens 6. On the rear surface of the transparent covering member 21, a black printed layer 212 is formed at the portion except ones corresponding to the capturing window 206 and the communication window 207.

The shutter button 23 is provided to be slidable on a switch pin 231(not shown) without slipping out from the switch pin, as shown in FIG. 9. The switch pin 231 is provided to be slidable on the case body 2 without slipping out from the case body. Around the switch pin 231, a compressed coil screw 232 (not shown) is provided between the shutter button 23 and the case body 2.

When pressing down the shutter button 23 against the biasing force of the compressed coil screw 232 and thereby pressing down the switch pin 231, the top end of the switch pin 231 is brought into contact with an electrode with a shape like teeth of a comb on the board 12. As a result, the shutter switch is changed to on to open the shutter of camera.

The shutter button 23 is biased by a compressed coil screw 233 which is disposed between the shutter button and the case body 2, in the projecting direction of the compressed coil screw at both ends thereof, as shown in FIGS. 8 and 9. Thus, the shutter button 23 is supported stably.

As described above, according to the embodiment of the invention, because the image capturing lens 6 and the infrared communication portion 7 are provided near to each other in

parallel, in the end side surface of the wristwatch 1, it is possible to capturing an image by pressing down the shutter button 23 which is arranged in this side and also to communicate data, while putting it on an arm and using the data display portion 22 as a monitor, i.e., a finder.

Because the portable electronic apparatus of the embodiment can be used in a state of placing the case body 2 on a stable table or the like, with overlapping the wrist band 3 on the rear surface of the case body 2, as shown by the two-dot chain line in FIG. 5, it is possible to capturing an image and to communicate data, in a state of placing the case body 2 on an appropriate stable place and directing it in an appropriate direction.

Because both the image capturing lens 6 and the infrared communication portion 7 are covered by a transparent covering member 21, it is possible to reduce the number of necessary components and the number of steps for assembling.

Further, because the transparent covering member 21 with a convex lens shape has a circular recess portion 211 on the front surface at a position corresponding to that of the image capturing lens 6 and has a black printed layer 212 on the rear surface thereof at portions except ones corresponding to the capturing window 206 and the communication window 207, it does not interfere optically with capturing images through the image capturing lens 6 nor exert an adverse optical influence upon the image capturing lens 6 and the infrared communication portion, e.g., interference of optical axes to each other.

The circular recess portion 211 of the transparent covering member 21 may have a lens structure. No cover 73 for infrared communication may be provided by making the transparent covering member 21 by a filter member and by
 5 reducing the filter property by the circular recess portion 211.

FIG. 11 is a bottom view of the case body 2 of the apparatus, and FIG. 12 is an exploded perspective view showing the case back 8, the O-ring 99 for waterproof, and the battery cover 9, which are attached to the rear surface of the case body 2 of the
 10 apparatus.

In the case back 8, an attachment hole 80 through which a battery can be attached is formed at the central portion, and a loop groove 81 for receiving a waterproof ring is formed in the surface around the attachment hole 80, as also shown in FIGS.
 15 14 to 16. In the periphery of the attachment hole 80, a pair of flanges 82 and 82 which are faced to each other in a radial direction to have a smaller diameter. Each of the flanges 82 is formed at an approximate angle of 90°. At an end in one direction of each flange 82, a small cut-out 83 is formed.

In the loop groove 81 for receiving a waterproof ring of the case back 8, the O-ring 99 is fitted. The case back 8 is fixed to the rear surface of the case body 2 at four corners by using screws 84, as shown in FIG. 11. Between the case body 2 and the case back 8, the O-ring 99 is provided, as shown in
 20 FIGS. 8 and 9.

As shown in FIGS. 13, 18 and 19, in the front surface of the battery cover 9, a radial direction recess 90 which extends

radially to pass through the center is formed, and in the rear surface thereof, a fitting portion 91 having a shape corresponding to the attachment hole 80 is provided. At the central portion of the fitting portion 91, a battery clamp 95 which comprises a pair of plate springs facing to each other is attached.

On the periphery of the fitting portion 91, a pair of small diameter portions 92 and 92 are formed radially to have a shape fitting in the pair of flanges 82 and 82 of the case back 8, and a pair of large diameter portions are formed radially next to the small diameter portions 92 and 92. Between each large diameter portion and the front surface of the battery cover 9, a circumferential groove 93 with a diameter which can receive the small diameter flange 82 of the case back 8 and is closed at the bottom end. In the middle of each large diameter portion, a small projection 94 is formed toward the circumferential groove 93 at a position corresponding to that of the small cut-out 83 when rotating to insert the small diameter flange 82 into the circumferential groove 93 to the bottom.

FIGS. 21A and 21B show the attachment relationship between the battery cover 9 and the case back 8, from the rear side, in which FIG. 21A is a view when inserting the battery cover 9 into the case back 8, and FIG. 21B is a view when rotating the battery cover 9 to lock to the case back 8.

In order to fix the battery cover 9 to the case back 8, the fitting portion 91 of the battery cover 9 is inserted into the attachment hole 80 of the case back 8, with fitting the small

diameter portions 92 and 92 into the small diameter flanges 82 of the case back 8.

Thereafter, the battery cover 9 is rotated in the direction of the arrow in FIG. 21A (from the operator's point of view, in the clockwise direction) by inserting a coin into the radial direction recess 90 to rotate it. Then, the small diameter flanges 82 of the case back 8 are being inserted into the circumferential groove 93 of the battery cover 9 while the O-ring 99 in the loop groove 81 is being compressed against the peripheral rear surface of the battery cover 9.

When the small projections 94 in the circumferential grooves 93 reach the positions of the small cut-outs 83 in the flanges 82 of the case back 8, the operator can know the fact that the battery cover 9 has reached the rotational fixation position, by a click feeling.

In order to take the battery cover 9 off the case back 8, it may reverse the order of steps.

SECOND EMBODIMENT

The second embodiment is different from the first embodiment in the following points.

In the portable image capturing device according to the second embodiment, the cover 73 for an infrared communication in the first embodiment is not used, a transparent covering member 121 having an infrared filtering property is adopted, as shown by oblique lines in FIG. 22. The circular recess portion 211 provided on the surface of the transparent covering

member 121 is formed to be thin than the rest portion, thereby it functions to reduce the infrared filtering property. In figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

According to use of the transparent covering member 121 having an infrared filtering property, it is possible to reduce the number of necessary parts because the cover 73 for an infrared communication used in the first embodiment is not required.

THIRD EMBODIMENT

The third embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the third embodiment, the cover 73 for an infrared communication in the first embodiment is not used, an infrared filtering seal 173 which is shown by oblique lines in FIG. 23, is adhered to the periphery of the front surface of the communication window 207 of the recess portion 205 for cover attachment, as shown in FIGS. 23 to 25. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

According to use of the infrared filtering seal 173

adhered, without the cover 73 for an infrared communication used in the first embodiment, it is possible to mount parts with high density and to make the portable image capturing device small-sized.

5

FOURTH EMBODIMENT

The fourth embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the fourth embodiment, the cover 10 73 for an infrared communication in the first embodiment is not used, a transparent covering member 221 which has an infrared filter characteristic form portion 2210 (the range of which is shown by oblique lines in FIG. 26) in the side of the communication window 207 is adopted instead thereof. The 15 transparent covering member 221 is produced by the two-color forming is used. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, 20 elements, portions or the like is omitted.

Because the side of the communication window 207 is covered by the infrared filter characteristic form portion 2210 of the transparent covering member 221 produced by the two-color forming, it is possible to reduce the number of necessary 25 parts because the cover 73 for an infrared communication used in the first embodiment is not required.

FIFTH EMBODIMENT

The fifth embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the fifth embodiment, the black printed layer 212 in the first embodiment is not used, a rib 208 processed for positioning the transparent covering member 321 is disposed between the capturing window 206 of the recess portion 205 for cover attachment and the communication window 207, as shown in FIGS. 30 and 31. The rib 208 also plays a role to prevent the image capturing lens 6 and the infrared communication portion 7 from being adversely affected optically. In the transparent covering member 321, a recess portion 322 corresponding to the rib 208 is formed. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

In this embodiment, because the black printed layer 212 in the first embodiment is not used and the recess portion 322 of the transparent covering member 321 is fitted to the rib 208 which is disposed between the capturing window 206 of the recess portion 205 for cover attachment and the communication window 207, it is possible to prevent the transparent covering member 321 from slipping off by shock. Such a structure make easy to assemble the transparent covering member 321 to the device body 2.

SIXTH EMBODIMENT

The sixth embodiment is different from the first embodiment in the following points. In the portable image capturing device according to the sixth embodiment, the image capturing portion and the infrared communication portion 701 are disposed in the device body (200) so that the camera direction for taking a photograph (Y-axis direction in FIGS. 32 and 33) by the image capturing lens 6 is approximately perpendicular to the infrared communication direction (X-axis direction in the figures) by the infrared communication portion 701. The side surfaces perpendicular to each other having the image capturing lens 6 and the infrared communication portion 701 are covered with a single transparent covering member 421. In FIG. 33, the reference numeral 702 denotes an apparatus for infrared communication, e.g., an infrared communication port apparatus which is connected to a PC. In the figures, the same numbers are attached to structural members, elements, portions or the like corresponding to those of the first embodiment. A detailed explanation for such corresponding structural members, elements, portions or the like is omitted.

According to this embodiment, because the camera direction for taking a photograph is approximately perpendicular to the infrared communication direction, in addition to the advantageous effects according to the first embodiment, it is possible to handle the device easily even in a condition of wearing the device on an arm while transmitting data by infrared communication, and to enable camera handling

to take a photograph by remote control (using infrared ray).

SEVENTH EMBODIMENT

The seventh embodiment is different from the first
 5 embodiment in the following points. In the portable image
 capturing device according to the seventh embodiment, the
 device body 250 comprises a single transparent covering member
 521 which covers both the data display portion (LCD) 521 and
 the side surface having the image capturing lens 6 and the
 10 infrared communication portion 7. In FIG. 34, the numeral 522
 denotes a display window. In FIG. 35, the numeral 529 denotes
 a bezel. In the figures, the same numbers are attached to
 structural members, elements, portions or the like
 corresponding to those of the first embodiment. A detailed
 15 explanation for such corresponding structural members,
 elements, portions or the like is omitted.

According to the embodiment, because a single transparent
 covering member 521 which covers both the data display portion
 (LCD) 521 and the side surface is provided, it is possible to
 20 reduce the number of necessary parts.

Although the apparatus of the invention is applied to a
 watch in the above-described embodiment, it is not limited to
 this, and the invention can be applied to any portable
 25 electronic apparatus (portable image capturing device), e.g.,
 a portable terminal and the like.

Also the structure or the like for the camera portion

(image capturing portion) and the optical communication portion (infrared communication portion) are not limited to that of the embodiment. It is of course that other concrete detailed structures or the like of the apparatus of the invention may
 5 be changed appropriately.

100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622
 623
 624
 625
 626
 627
 628
 629
 630
 631
 632
 633
 634
 635
 636
 637
 638
 639
 640
 641
 642
 643
 644
 645
 646
 647
 648
 649
 650
 651
 652
 653
 654
 655
 656
 657
 658
 659
 660
 661
 662
 663
 664
 665
 666
 667
 668
 669
 670
 671
 672
 673
 674
 675
 676
 677
 678
 679
 680
 681
 682
 683
 684
 685
 686
 687
 688
 689
 690
 691
 692
 693
 694
 695
 696
 697
 698
 699
 700
 701
 702
 703
 704
 705
 706
 707
 708
 709
 710
 711
 712
 713
 714
 715
 716
 717
 718
 719
 720
 721
 722
 723
 724
 725
 726
 727
 728
 729
 730
 731
 732
 733
 734
 735
 736
 737
 738
 739
 740
 741
 742
 743
 744
 745
 746
 747
 748
 749
 750
 751
 752
 753
 754
 755
 756
 757
 758
 759
 760
 761
 762
 763
 764
 765
 766
 767
 768
 769
 770
 771
 772
 773
 774
 775
 776
 777
 778
 779
 780
 781
 782
 783
 784
 785
 786
 787
 788
 789
 790
 791
 792
 793
 794
 795
 796
 797
 798
 799
 800
 801
 802
 803
 804
 805
 806
 807
 808
 809
 810
 811
 812
 813
 814
 815
 816
 817
 818
 819
 820
 821
 822
 823
 824
 825
 826
 827
 828
 829
 830
 831
 832
 833
 834
 835
 836
 837
 838
 839
 840
 841
 842
 843
 844
 845
 846
 847
 848
 849
 850
 851
 852
 853
 854
 855
 856
 857
 858
 859
 860
 861
 862
 863
 864
 865
 866
 867
 868
 869
 870
 871
 872
 873
 874
 875
 876
 877
 878
 879
 880
 881
 882
 883
 884
 885
 886
 887
 888
 889
 890
 891
 892
 893
 894
 895
 896
 897
 898
 899
 900
 901
 902
 903
 904
 905
 906
 907
 908
 909
 910
 911
 912
 913
 914
 915
 916
 917
 918
 919
 920
 921
 922
 923
 924
 925
 926
 927
 928
 929
 930
 931
 932
 933
 934
 935
 936
 937
 938
 939
 940
 941
 942
 943
 944
 945
 946
 947
 948
 949
 950
 951
 952
 953
 954
 955
 956
 957
 958
 959
 960
 961
 962
 963
 964
 965
 966
 967
 968
 969
 970
 971
 972
 973
 974
 975
 976
 977
 978
 979
 980
 981
 982
 983
 984
 985
 986
 987
 988
 989
 990
 991
 992
 993
 994
 995
 996
 997
 998
 999
 1000